

# **German Railway Turnout**

ドイツ鉄道軌道セット(待避レール)

德国铁路道岔

#### PLEASE READ BEFORE OPERATION!

- Tools recommended as below: (Not included)
  Adhesives; Paints; Side Cutters; Sharp Edged Pliers; Modeling Knife; Modeling
- File: Nippers; Drill: Scissors; Sand Paper, Soft Cloth; Cyanoacrylate Glue.
- \* Make sure to read this instruction listed below before assembling.
- \* The kit contains the small parts, they can be dangerous if swallowed by mistake, so keep them away from reach of children.
- \* Cut the all parts off carefully and remove the waste parts into the garbage can.
- \* More caution and care should be needed for cutting and handling the photo etched parts.
- \* Make attention that some parts should be attached the decal when assembled.
- \* During assembling, please tear up and throw away the plastic bags, or may cause the dangerous if wearing over head by children's mistake.
- \* When using the adhesives and paints, please do not use them in the closed room or near the fire, also must be very careful to protect your eyes,face and clothes.
- \* Adult supervised when assembled by children under 14 years old.

## 装配前请仔细阅读:

- \*推荐使用的模型工具(请自备): 专用模型胶水、专用模型油漆,水口剪刀、长咀钳、刀片、 锉刀,镊子钳、钻、剪刀,软布,砂纸,瞬间快干胶等。
- \*用水口剪刀或刀片小心切下所有塑胶零件和蚀刻片零件, 不要遗失小零件。
- \* 切取蚀刻片时应特别注意防止利边划伤手指。
- \* 用模型锉刀小心锉平所有零件表面的注射浇口。
- \* 用适量的强力快干胶水粘合蚀刻片零件和金属轴,切忌过量,否则可能导致可动零件被粘住。
- \*注意某些零件表面需在装配时同步贴上水贴纸。
- ★制作时应远离幼儿并将包装袋及时收妥,谨防小孩玩耍 而引起意外。



cyanoacrylate glue 强力胶



weight



make hole 钻孔



cut / remove 切除 ?

option

X

no cement 不涂胶水

deca



bend




repair 填补


## The method to apply the decals


- 1.Cut off the decal from the decal paper and put it into the warm water 40  $^{\rm C}$  for 10 seconds.
- 2. Take the decal from the water and put it on a piece of clean cloth.
- 3. Remove the decal slowly from the paper to the targeted location by a wet finger.
- 4. Use a piece of dry and soft cloth to press it gently on the decal until it getting dry and no bubble existing.


#### 水贴纸的使用方法:


- 一.把相关的印花从水贴纸上剪下,放入40℃左右的 温水中浸10秒。
- 二. 然后将印花放在干净的布上。
- 三.拿上印花纸板、手指蘸水将印花移到适当的位置。
- 四.用软干布轻压印花直至水干,气泡消失。





















(8-8)



hobbyidhila



ROAD-E

# 部品图 parts B C 1 1 1 1 1 1 1 1 1 A A A A A A A ROAD-G D BEREE ន់ដង់ដ arar i i ROAD-F H H H ROAD-E ROAD-D ROAD-C 10 10 10 W W W . # # # # H ...