
# M3A1 LEE US MEDIUM PORK



The outbreak of WWII in Europe caused the U.S. Army to beginning in December, and the first units becoming our immediate demand for more medium tanks. The main use top, which was a compromise meant to produce a tart is configuration and crew size. Tanks fitted with the U.S. Switch known as the "Grant", named after Union General Ulysteincluding a high silhouette, and the sponson muniting the produced with a large cast hull, and much use in the armored recovery vehicle, the M7 Priest shall oppelled up

The Hunsel Cking an effective tank force. Design of the Medium tank M3 commenced in July 1940, with production had be 11. The U.S. Army required a tank armed with a 75mm main gun and the United Kingdom had made an with call mounted the 75mm main gun in the right sponson, with another 37mm gun mounted in a small turret on it is lossible until the M4 became available. In Great Britain the tank was called by two names based on the turret et vire called the "Lee", named after Confederate General Robert E. Lee. Variants using British style turrets were style to the M3 offered potent firepower and sturdy armor, but had serious shortcomings in it's design and shape, in hain gun, which limited the traverse and prevented the tank from taking a hull-down position. 300 tanks were for training purposes. Multiple variants and derivatives were spawned from M3 production, including the M31 cDL (Canal Defense Light), and the Canadian RAM cruiser tank.

03.02.2114



## **CAUTION**

- Read carefully and fully understand the instructions before commencing assembly.
  A supervising adult should also read the instructions if a child assembles the model.
- When assembling this kit, tools including knives used. Extra care should be taken to
- avoid personal injury.
- Keep out of reach of small children. Children must not be allowed to suck any part, or pull vinyl bag over their heads.





















Heating Instant Glue for Metal Optional

Color info and profiles by Mill sime lez




















# APPLYING DECALS

- 1.Clean the model surface with a wet cloth.
- 2.Cut out each decal design from sheet, and dip it in tepid water for 15~20 sec.
- 3. Hold the backing sheet edge and slide decal onto the model.
- 4. Move decal into position by wetting decal with finger.
- 5.Press decal gently down with a soft cloth until excess water and air bubbles are gone.





Be careful not to hurt when removing PE parts.





Secure using instant glue (not included).




Finish using file.
































Lover Hull





TP

Decal

